

# Summary of product characteristics for a biocidal product

**Product name:** Aqua Combi WA D20

**Product type(s):** PT08 - Wood preservatives (Preservatives)

**Authorisation number:** EE-NAMR2016-0060

**R4BP 3 asset reference number:** EE-0012460-0000

## Table Of Contents

Administrative information	1
1.1. Trade names of the product	1
1.2. Authorisation holder	1
1.3. Manufacturer(s) of the biocidal products	1
1.4. Manufacturer(s) of the active substance(s)	1
2. Product composition and formulation	2
2.1. Qualitative and quantitative information on the composition of the biocidal product	2
2.2. Type of formulation	2
3. Hazard and precautionary statements	2
4. Authorised use(s)	3
5. General directions for use	4
5.1. Instructions for use	4
5.2. Risk mitigation measures	4
5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment	5
5.4. Instructions for safe disposal of the product and its packaging	5
5.5. Conditions of storage and shelf-life of the product under normal conditions of storage	5
6. Other information	5

## Administrative information

### 1.1. Trade names of the product

Aqua Combi WA D20
-------------------

### 1.2. Authorisation holder

<b>Name and address of the authorisation holder</b>	Name	Akzo Nobel Industrial Coatings AB
	Address	Staffanstorpsvägen 50 20517 Malmö Sweden
<b>Authorisation number</b>	EE-NAMR2016-0060	
<b>R4BP 3 asset reference number</b>	EE-0012460-0000	
<b>Date of the authorisation</b>	08/02/2016	
<b>Expiry date of the authorisation</b>	30/10/2025	

### 1.3. Manufacturer(s) of the biocidal products

<b>Name of the manufacturer</b>	Akzo Nobel Industrial Coatings AB
<b>Address of the manufacturer</b>	Staffanstorpsvägen 50 20517 Malmö Sweden
<b>Location of manufacturing sites</b>	Staffanstorpsvägen 50 20517 Malmö Sweden

### 1.4. Manufacturer(s) of the active substance(s)

<b>Active substance</b>	39 - 3-iodo-2-propynylbutylcarbamate (IPBC)
<b>Name of the manufacturer</b>	TROY Chemical Corporation
<b>Address of the manufacturer</b>	One Avenue L NJ 07105 Newark United States
<b>Location of manufacturing sites</b>	12 e Uiverlaan 3145 Maassluis Netherlands

## 2. Product composition and formulation

### 2.1. Qualitative and quantitative information on the composition of the biocidal product

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		Active Substance	55406-53-6	259-627-5	0,295
Isothiazolone preparation					0,09
Isothiazolone preparation					0,0042
2-Butoxyethanol (Butyl glycol)			111-76-2	203-905-0	1,9
Isothiazolone preparation					0,0028

### 2.2. Type of formulation

Water based primer
--------------------

## 3. Hazard and precautionary statements

<b>Hazard statements</b>	<p>Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) and 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.</p> <p>Harmful to aquatic life with long lasting effects.</p>
<b>Precautionary statements</b>	<p>Avoid release to the environment.</p> <p>Dispose of container to in accordance with all local, regional, national and international</p>

regulations.

## 4. Authorised use(s)

### 4.1 Use description

#### Use 1 - Ready-to-use wood preservative primer

<b>Product type</b>	PT08 - Wood preservatives (Preservatives)
<b>Where relevant, an exact description of the authorised use</b>	For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), carports, shutters and balcony railings. Not for indoor use.
<b>Target organism(s) (including development stage)</b>	Scientific name: Aureobasidium pullulans spp. Common name: Sapstain fungi Development stage:
<b>Field(s) of use</b>	Outdoor
<b>Application method(s)</b>	automated spraying - professional user: automated spraying with adequate equipment industrial user: automated spraying with adequate equipment
<b>Application rate(s) and frequencies</b>	Apply 250 - 300 ml/m <sup>2</sup> (308 - 370 g/m <sup>2</sup> ) by 2 applications - 100 - Apply 250 -300 ml/m <sup>2</sup> (308 - 370 g/m <sup>2</sup> ) by 2 applications. The drying time is 18 - 24 hours (20°C / 55% rel. humidity)
<b>Category(ies) of users</b>	Professional Industrial
<b>Pack sizes and packaging material</b>	Can /Tin - Metal: - 20L Drum - Plastic: HDPE - 120L IBC (intermediate bulk container) - Plastic: HDPE - 1000L

#### 4.1.1 Use-specific instructions for use

#### 4.1.1 Use-specific instructions for use

Wood surfaces must be clean and dry before treating. Handle product and dry freshly treated wood in areas with good ventilation. Keep freshly treated wood roofed or otherwise protected against rain until complete dryness. Do not breathe sanding dust. The paint is ready to use. Do not thin. Stir well before use. Apply by spraying. Reseal container after use. Processing temperature is 20 - 25°C. The drying time is 18 - 24 hours (20°C / 55% rel. humidity).

#### 4.1.2 Use-specific risk mitigation measures

Avoid contact with skin and eyes. Wear suitable protective clothing, gloves and eye/face protection.

#### 4.1.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

The precautions generally recommended for handling wood protection products should be observed.  
After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.  
After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur.  
If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter lungs. Get medical attention.  
After inhalation: Move affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

#### 4.1.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

European waste code (EWC): 03 02 05: Other wood preservatives containing dangerous substances.

#### 4.1.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

Store product in tightly closed original containers at temperatures about 15 - 25°C. The product is stable for 2 years at room temperature.

### 5. General directions for use

#### 5.1. Instructions for use

Wood surfaces must be clean and dry before treating. Handle product and dry freshly treated wood in areas with good ventilation. Keep freshly treated wood roofed or otherwise protected against rain until complete dryness. Do not breathe sanding dust. The paint is ready to use. Do not thin. Stir well before use. Apply by spraying. Reseal container after use. Processing temperature is 20 - 25°C. Apply 250 - 300 ml/m<sup>2</sup> (308 - 370 g/m<sup>2</sup>) by 2 coats (depending on wood species). The drying time is 18 - 24 hours (20°C / 55% rel. humidity).

#### 5.2. Risk mitigation measures

Avoid contact with skin and eyes. Wear suitable protective clothing, gloves and eye/face protection.

### **5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment**

The precautions generally recommended for handling wood protection products should be observed.  
After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms.  
After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur.  
If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.  
After inhalation: Move affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

### **5.4. Instructions for safe disposal of the product and its packaging**

European waste code (EWC): 03 02 05: Other wood preservatives containing dangerous substances.

### **5.5. Conditions of storage and shelf-life of the product under normal conditions of storage**

Store product in tightly closed original container at temperatures about 15 - 25°C. The product is stable for 2 years at room temperature.

## **6. Other information**

Use biocides safely. Always read label and product information before use.