

ΕΛ

ΠΑΡΑΡΤΗΜΑ

ΠΕΡΙΛΗΨΗ ΤΩΝ ΧΑΡΑΚΤΗΡΙΣΤΙΚΩΝ ΤΟΥ ΠΡΟΪΟΝΤΟΣ ΓΙΑ ΒΙΟΚΤΟΝΟ

Sikkens Cetol HLS plus (BP) (Teak)

Τύπος(οι) προϊόντος

PT08: Συντηρητικά ξύλου

Αριθμός άδειας: ΤΠ8-0117-ΟΠ 1-1

Αριθμός κανονιστικού πόρου R4BP: GR-0020417-0005

1. ΔΙΟΙΚΗΤΙΚΕΣ ΠΛΗΡΟΦΟΡΙΕΣ	3
1.1. Εμπορική(ές) ονομασία(ες) του προϊόντος	3
1.2. Κάτοχος άδειας	3
1.3. Παρασκευαστής(ές) του προϊόντος	3
1.4. Παρασκευαστής(-ές) της(των) δραστικής(ών) ουσίας(ών)	3
2. ΣΥΝΘΕΣΗ ΚΑΙ ΤΥΠΟΠΟΙΗΣΗ ΠΡΟΪΟΝΤΟΣ	4
2.1. Ποιοτικές και ποσοτικές πληροφορίες για τη σύνθεση του προϊόντος	4
2.2. Τύπο(οι) τυποποίησης	4
3. ΔΗΛΩΣΕΙΣ ΕΠΙΚΙΝΔΥΝΟΤΗΤΑΣ ΚΑΙ ΠΡΟΦΥΛΑΞΗΣ	5
4. ΕΓΚΕΚΡΙΜΕΝΕΣ ΧΡΗΣΕΙΣ	6
4.1. Περιγραφή χρήσης	6
5. ΓΕΝΙΚΕΣ ΟΔΗΓΙΕΣ ΧΡΗΣΗΣ	8
5.1. Οδηγίες χρήσης	8
5.2. Μέτρα μετριασμού κινδύνου	9
5.3. Στοιχεία των πιθανών άμεσων ή έμμεσων επιπτώσεων, οδηγίες πρώτων βοηθειών και επείγοντα μέτρα για την προστασία του περιβάλλοντος	10
5.4. Οδηγίες για την ασφαλή τελική διάθεση του προϊόντος και της συσκευασίας του	13
5.5. Συνθήκες αποθήκευσης και διάρκεια ζωής του προϊόντος υπό κανονικές συνθήκες αποθήκευσης	14
6. ΑΛΛΕΣ ΠΛΗΡΟΦΟΡΙΕΣ	17

Κεφάλαιο 1. ΔΙΟΙΚΗΤΙΚΕΣ ΠΛΗΡΟΦΟΡΙΕΣ

1.1. Εμπορική(ές) ονομασία(ες) του προϊόντος

Εμπορική ονομασία	Sikkens Cetol HLS plus(BP) Teak SADOLIN Classic HP (BPR) teak SADOLIN IMPREGNAT Classic HP + Tek SADOLIN CLASSIC + Tek SADOLIN IMPREGNAT CLASSIC + Tek SADOLIN Classic HP + Tek Sikkens Cetol HLS plus (BPR) Teak Xyladecor Holzschutzlasur BP Teak Sikkens Cetol HLS plus (BPR) Teak
-------------------	---

1.2. Κάτοχος άδειας

Επωνυμία και διεύθυνση του κατόχου άδειας	Όνομασία	Akzo Nobel Decorative Coatings B.V.
	Διεύθυνση	Christian Neefstraat 2 - Attn. Director PSRAQ 1077 WW Amsterdam άλλο: Netherlands
Αριθμός άδειας	ΤΠ8-0117-ΟΠ 1-1	
Αριθ. αναφ. στοιχείου στο μητρώο βιοκτόνων <i>R4BP</i>	GR-0020417-0005	
Ημερομηνία έκδοσης της άδειας	13/02/2018	
Ημερομηνία λήξης της άδειας	30/10/2025	

1.3. Παρασκευαστής(ές) του προϊόντος

1.4. Παρασκευαστής(-ές) της(των) δραστικής(ών) ουσίας(ών)

Δραστική ουσία	Βουτυλοκαρβαμιδικό 3-ιωδο-2-προπυνύλιο (IPBC)
Επωνυμία παρασκευαστή	TROY Corporation
Διεύθυνση παρασκευαστή	8 Vreeland Road, Florham Park 07932 New Jersey Ηνωμένες Πολιτείες της Αμερικής
Τοποθεσία των εγκαταστάσεων παραγωγής	One Avenue L NJ 07105 Newark Ηνωμένες Πολιτείες της Αμερικής

Δραστική ουσία	Βουτυλοκαρβαμιδικό 3-ιωδο-2-προπυνύλιο (IPBC)
Επωνυμία παρασκευαστή	TROY Chemical Corporation
Διεύθυνση παρασκευαστή	One Avenue L NJ 07105 Newark Ηνωμένες Πολιτείες της Αμερικής
Τοποθεσία των εγκαταστάσεων παραγωγής	12e Uiverlaan 3145 Maassluis Κάτω Χώρες

Κεφάλαιο 2. ΣΥΝΘΕΣΗ ΚΑΙ ΤΥΠΟΠΟΙΗΣΗ ΠΡΟΪΟΝΤΟΣ

2.1. Ποιοτικές και ποσοτικές πληροφορίες για τη σύνθεση του προϊόντος

Κοινή ονομασία	Ονομασία κατά IUPAC	Λειτουργία	Αριθμός CAS	Αριθμός ΕΚ	Περιεκτικότητα (%)
Βουτυλοκαρβαμικό 3-ιωδο-2-προπυνύλιο (IPBC)		δραστική ουσία	55406-53-6	259-627-5	0,7

2.2. Τύπο(οι) τυποποίησης

AL Κάθε άλλο υγρό

Κεφάλαιο 3. ΔΗΛΩΣΕΙΣ ΕΠΙΚΙΝΔΥΝΟΤΗΤΑΣ ΚΑΙ ΠΡΟΦΥΛΑΞΗΣ

Δηλώσεις επικινδυνότητας	<p>H412: Επιβλαβές για τους υδρόβιους οργανισμούς, με μακροχρόνιες επιπτώσεις.</p> <p>EUH066: Παρατεταμένη έκθεση μπορεί να προκαλέσει ξηρότητα δέρματος ή σκάσιμο.</p> <p>EUH208: Περιέχει <name of sensitising substance>. Μπορεί να προκαλέσει αλλεργική αντίδραση.</p>
Δηλώσεις προφύλαξης	<p>P101: Εάν ζητήσετε ιατρική συμβουλή, να έχετε μαζί σας τον περιέκτη του προϊόντος ή την ετικέτα.</p> <p>P102: Μακριά από παιδιά.</p> <p>P262: Να μην έρθει σε επαφή με τα μάτια, με το δέρμα ή με τα ρούχα.</p> <p>P273: Να αποφεύγεται η ελευθέρωση στο περιβάλλον.</p> <p>P312: Καλέστε το το ΚΕΝΤΡΟ ΔΗΛΗΤΗΡΙΑΣΕΩΝ εάν αισθανθείτε αδιαθεσία.</p> <p>P501: Διάθεση του περιεχομένου σε local rules.</p> <p>P312: Καλέστε το το ΚΕΝΤΡΟ ΔΗΛΗΤΗΡΙΑΣΕΩΝ εάν αισθανθείτε αδιαθεσία.</p> <p>P501: Διάθεση του περιέκτη σε local rules.</p>

Κεφάλαιο 4. ΕΓΚΕΚΡΙΜΕΝΕΣ ΧΡΗΣΕΙΣ

4.1. Περιγραφή χρήσης

Πίνακας 1. Κατά των μυκήτων αποχρωματισμού του ξύλου

Τύπος προϊόντος	PT08: Συντηρητικά ξύλου
Ακριβής περιγραφή της εγκεκριμένης χρήσης, εάν απαιτείται	Το συντηρητικό προορίζεται για χρήση σε εξωτερικά ξύλα, τα οποία δεν είναι σε άμεση επαφή με το έδαφος ή με νερό και εκτίθενται στις καιρικές συνθήκες, π.χ. σε παράθυρα, πόρτες (εσωτερικά και εξωτερικά μέρη), υπόστεγα, πέργκολες, παντζούρια και κάγκελα μπαλκονιού. Όχι για χρήση σε ξυλεία που βρίσκεται σε εσωτερικούς χώρους.
Στοχευόμενος(οι) οργανισμός(οί) (συμπεριλαμβανομένου του σταδίου ανάπτυξης)	Επιστημονική ονομασία: <i>Aureobasidium pullulans</i> spp. Κοινή ονομασία: sapstain fungi Στάδιο ανάπτυξης: Κανένα δεδομένο
Πεδίο(α) χρήσης	χρήση σε εσωτερικό χώρο χρήση σε εξωτερικό χώρο
Μέθοδος(οι) εφαρμογής	Μέθοδος: Ανοιχτό σύστημα: εφαρμογή με πινέλο Λεπτομερής περιγραφή: Μη διαθέσιμη
Ποσοστό(ά) και συχνότητα εφαρμογής	Δόση εφαρμογής: 200-250 ml/m ² Αραίωση (%): - Αριθμός εφαρμογών και χρόνος εφαρμογής: 200-250 g/m ²
Κατηγορία(ες) χρηστών	επαγγελματίας ; ευρύ κοινό (μη επαγγελματίες)
Μεγέθη συσκευασίας και υλικό συσκευασίας	Δοχείο μεταλλικό 0.75L - 20L (0.75L; 1L; 2.5L; 3L; 5L; 5.5L; 6L; 9L; 9.5L; 10L; 11L; 11.5L; 12L; 20L)

4.1.1. Οδηγίες χρήσης ανά χρήση

Φυλάξτε το μακριά από παιδιά. Να φοράτε προστατευτικά ρούχα και γάντια.

Χρησιμοποιήστε τα βιοκτόνα με ασφάλεια. Να διαβάσετε πάντα την ετικέτα και τις πληροφορίες προϊόντος πριν από τη χρήση

4.1.2. Μέτρα μετριασμού κινδύνου ανά χρήση

-

4.1.3. Στοιχεία των πιθανών άμεσων ή έμμεσων επιπτώσεων, οδηγίες πρώτων βοηθειών και επείγοντα μέτρα για την προστασία του περιβάλλοντος που σχετίζονται με τη χρήση

Σε περίπτωση επαφής με το δέρμα: Βγάλτε αμέσως όλα τα μολυσμένα ρούχα και πλυθείτε αμέσως με πολύ νερό και σαπούνι. Ζητήστε ιατρική συμβουλή εάν τα συμπτώματα επιμένουν.

Σε περίπτωση επαφής με τα μάτια: Πλύνετε τα αμέσως με άφθονο νερό. Ζητήστε ιατρική συμβουλή εάν τα συμπτώματα επιμένουν.

Σε περίπτωση κατάποσης: Μην προκαλέσετε εμετό εκτός αν σας δόθηκαν ρητές οδηγίες από ιατρικό προσωπικό. Αν προκληθεί εμετός θα πρέπει να κρατάτε το κεφάλι χαμηλά ώστε να μην εισέλθει ο εμετός στους πνεύμονες.

Σε περίπτωση εισπνοής: Μεταφέρετε τον παθόντα στον καθαρό αέρα. Διατηρήστε τον ζεστό και αφήστε τον να ξεκουραστεί. Να του παρασχεθεί τεχνητή αναπνοή από εκπαιδευμένο άτομο σε περίπτωση μη κανονικής αναπνοής ή αναπνευστικής δυσχέρειας. Ζητήστε ιατρική συμβουλή εάν τα

συμπτώματα είναι σοβαρά ή διαρκούν πολύ. Αν είναι αναισθητος τοποθετήστε τον σε θέση ανάνηψης και ζητήστε αμέσως ιατρική βοήθεια..

Τηλ Κέντρου Δηλητηριάσεων: 210 7793777

4.1.4. Οδηγίες για την ασφαλή τελική διάθεση του προϊόντος και της συσκευασίας του που σχετίζονται με τη χρήση

Το υλικό αυτό και ο περιέκτης του θα πρέπει να διατίθενται με ασφαλή τρόπο.

4.1.5. Συνθήκες αποθήκευσης και διάρκεια ζωής του προϊόντος υπό κανονικές συνθήκες αποθήκευσης που σχετίζονται με τη χρήση

Αποθηκεύστε το προϊόν στα ερμητικά κλεισμένα αρχικά δοχεία σε θερμοκρασίες μεταξύ 5-30 ° C.

Διάρκεια ζωής έως 36 μήνες

Κεφάλαιο 5. ΓΕΝΙΚΕΣ ΟΔΗΓΙΕΣ ΧΡΗΣΗΣ¹

5.1. Οδηγίες χρήσης

Sikkens Cetol HLS plus(BP)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Hazel)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Boxwood)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Blue)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Ebony)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Teak)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Dark Oak)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Pine)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Oregon)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Colourless)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Olive Green)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Cedar)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Fir green)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Mahogany)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Chestnut)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Light Oak)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

¹Οι οδηγίες χρήσης, τα μέτρα περιορισμού των κινδύνων και άλλες οδηγίες χρήσης που περιλαμβάνονται στην παρούσα ενότητα ισχύουν για οποιοδήποτε εγκεκριμένες χρήσεις.

Sikkens Cetol HLS plus (BP) (Old Pine)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Larch)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Rosewood)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

Sikkens Cetol HLS plus (BP) (Russian Green)

For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and out parts), carports, shutters and balcony railings. Not for indoor use.

5.2. Μέτρα μετριασμού κινδύνου

Sikkens Cetol HLS plus(BP)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Hazel)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Boxwood)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Blue)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Ebony)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Teak)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Dark Oak)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Pine)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Oregon)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Colourless)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Olive Green)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Cedar)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Fir green)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Mahogany)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Chestnut)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Light Oak)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Old Pine)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Larch)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Rosewood)

Keep out of reach of children. Wear suitable protective clothing and gloves.

Sikkens Cetol HLS plus (BP) (Russian Green)

Keep out of reach of children. Wear suitable protective clothing and gloves.

5.3. Στοιχεία των πιθανών άμεσων ή έμμεσων επιπτώσεων, οδηγίες πρώτων βοηθειών και επείγοντα μέτρα για την προστασία του περιβάλλοντος

Sikkens Cetol HLS plus(BP)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur.

If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

After inhalation: Move affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Hazel)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Boxwood)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Blue)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Ebony)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Teak)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Dark Oak)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Pine)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Oregon)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Colourless)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Olive Green)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Cedar)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Fir green)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Mahogany)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Chestnut)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Light Oak)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Old Pine)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Larch)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Rosewood)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If

swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

Sikkens Cetol HLS plus (BP) (Russian Green)

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur. If

swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

5.4. Οδηγίες για την ασφαλή τελική διάθεση του προϊόντος και της συσκευασίας του

Sikkens Cetol HLS plus(BP)

European waste code (EWC): 03 02 05: other wood preservatives containing dangerous substances / 20 01 27: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Hazel)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Boxwood)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Blue)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Ebony)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Teak)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Dark Oak)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Pine)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Oregon)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Colourless)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Olive Green)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Cedar)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Fir green)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Mahogany)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Chestnut)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Light Oak)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Old Pine)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Larch)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Rosewood)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

Sikkens Cetol HLS plus (BP) (Russian Green)

European waste code (EWC): 02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

5.5. Συνθήκες αποθήκευσης και διάρκεια ζωής του προϊόντος υπό κανονικές συνθήκες αποθήκευσης

Sikkens Cetol HLS plus(BP)

Store product in tightly closed original containers at temperatures about 5 - 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Hazel)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Boxwood)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Blue)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Ebony)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Teak)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Dark Oak)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Pine)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Oregon)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Colourless)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Olive Green)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Cedar)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Fir green)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Mahogany)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Chestnut)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Light Oak)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Old Pine)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Larch)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Rosewood)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Sikkens Cetol HLS plus (BP) (Russian Green)

Store product in tightly closed original containers at temperatures about 5 – 30°C. The product is stable for 3 years at room temperature.

Κεφάλαιο 6. ΑΛΛΕΣ ΠΛΗΡΟΦΟΡΙΕΣ

-