

Summary of product characteristics for a biocidal product

Product name: Aqua Combi WA D20

Product type(s): PT08 - Wood preservatives (Preservatives)

Authorisation number: BPD-reg. nr. 825-8

R4BP 3 asset reference number: DK-0001450-0000

Table Of Contents

Administrative information	1
1.1. Trade names of the product	1
1.2. Authorisation holder	1
1.3. Manufacturer(s) of the biocidal products	1
1.4. Manufacturer(s) of the active substance(s)	1
2. Product composition and formulation	2
2.1. Qualitative and quantitative information on the composition of the biocidal product	2
2.2. Type of formulation	2
3. Hazard and precautionary statements	2
4. Authorised use(s)	3
5. General directions for use	4
5.1. Instructions for use	4
5.2. Risk mitigation measures	4
5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment	4
5.4. Instructions for safe disposal of the product and its packaging	5
5.5. Conditions of storage and shelf-life of the product under normal conditions of storage	5
6. Other information	5

Administrative information

1.1. Trade names of the product

Aqua Combi WA D20

1.2. Authorisation holder

Name and address of the authorisation holder	Name	Akzo Nobel Industrial Coatings AB
	Address	Staffanstorpsvägen 50 20517 Malmö Sweden
Authorisation number	BPD-reg. nr. 825-8	
R4BP 3 asset reference number	DK-0001450-0000	
Date of the authorisation	25/11/2011	
Expiry date of the authorisation	30/10/2025	

1.3. Manufacturer(s) of the biocidal products

Name of the manufacturer	Akzo Nobel Industrial Coatings AB
Address of the manufacturer	Staffanstorpsvägen 50 20517 Malmö Sweden
Location of manufacturing sites	Staffanstorpsvägen 50 20517 Malmö Sweden

1.4. Manufacturer(s) of the active substance(s)

Active substance	39 - 3-iodo-2-propynylbutylcarbamate (IPBC)
Name of the manufacturer	TROY Chemical Corporation
Address of the manufacturer	One Avenue L NJ 07105 Newark United States
Location of manufacturing sites	12 e Uiverlaan 3145 Maassluis Netherlands

2. Product composition and formulation

2.1. Qualitative and quantitative information on the composition of the biocidal product

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		Active Substance	55406-53-6	259-627-5	0,295

2.2. Type of formulation

Water based primer

3. Hazard and precautionary statements

Hazard statements	<p>Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) and 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.</p> <p>Harmful to aquatic life with long lasting effects.</p>
Precautionary statements	<p>Avoid release to the environment.</p> <p>Dispose of container to in accordance with all local, regional, national and international regulations.</p>

4. Authorised use(s)

4.1 Use description

Use 1 - Ready-to-use wood preservative primer

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), carports, shutters and balcony railings. Not for indoor use.
Target organism(s) (including development stage)	Scientific name: Aureobasidium pullulans spp. Common name: Sapstain fungi Development stage:
Field(s) of use	Outdoor
Application method(s)	automated spraying - professional user: automated spraying with adequate equipment industrial user: automated spraying with adequate equipment
Application rate(s) and frequencies	Apply 250 - 300 ml/m ² (308 - 370 g/m ²) by 2 applications - 0 - Apply 250 -300 ml/m ² (308 - 370 g/m ²) by 2 applications. The drying time is 18 - 24 hours (20°C / 55% rel. humidity)
Category(ies) of users	Professional Industrial
Pack sizes and packaging material	Can /Tin, Metal: , 20L Drum, Plastic: HDPE , 120L IBC (intermediate bulk container), Plastic: HDPE , 1000L

4.1.1 Use-specific instructions for use

Wood surfaces must be clean and dry before treating. Handle product and dry freshly treated wood in areas with good ventilation. Keep freshly treated wood roofed or otherwise protected against rain until complete dryness. Do not breathe sanding dust. The paint is ready to use. Do not thin. Stir well before use. Apply by spraying. Reseal container after use. Processing temperature is 20 - 25°C. The drying time is 18 - 24 hours (20°C / 55% rel. humidity).

4.1.2 Use-specific risk mitigation measures

Avoid contact with skin and eyes. Wear suitable protective clothing, gloves and eye/face protection.

4.1.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

The precautions generally recommended for handling wood protection products should be observed.
After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.
After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur.
If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter lungs. Get medical attention.
After inhalation: Move affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

4.1.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

European waste code (EWC): 03 02 05: Other wood preservatives containing dangerous substances.

4.1.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

Store product in tightly closed original containers at temperatures about 15 - 25°C. The product is stable for 2 years at room temperature.

5. General directions for use

5.1. Instructions for use

Wood surfaces must be clean and dry before treating. Handle product and dry freshly treated wood in areas with good ventilation. Keep freshly treated wood roofed or otherwise protected against rain until complete dryness. Do not breathe sanding dust. The paint is ready to use. Do not thin. Stir well before use. Apply by spraying. Reseal container after use. Processing temperature is 20 - 25°C. Apply 250 - 300 ml/m² (308 - 370 g/m²) by 2 coats (depending on wood species). The drying time is 18 - 24 hours (20°C / 55% rel. humidity).

5.2. Risk mitigation measures

Avoid contact with skin and eyes. Wear suitable protective clothing, gloves and eye/face protection.

5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

The precautions generally recommended for handling wood protection products should be observed.
After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms.
After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur.
If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.
After inhalation: Move affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

5.4. Instructions for safe disposal of the product and its packaging

European waste code (EWC): 03 02 05: Other wood preservatives containing dangerous substances.

5.5. Conditions of storage and shelf-life of the product under normal conditions of storage

Store product in tightly closed original container at temperatures about 15 - 25°C. The product is stable for 2 years at room temperature.

6. Other information

Use biocides safely. Always read label and product information before use.

I. Etiketten skal udformes i overensstemmelse med artikel 69 i biocidforordningen (Forordning (EU) nr. 528/2012), og CLP Forordningen[1] .

II. Det er udelukkende ansøgers/godkendelsesindehaverens ansvar, at etiket, mærkning og pakning lever op til lovens krav, jf. biocidforordningen artikel 69.
Nedenstående tekst i afsnit III er bidrag til overholdelsen af reglerne og således kun en del af de krav, som stilles til blandt andet etiketten.

III. Etiketten skal indeholde nedenstående oplysninger. Oplysninger i citationstegn skal angives ordret:

1) I hovedfeltet:

"Træbeskyttelsesmiddel (PT8)

Må kun anvendes over jord til træbeskyttelse mod blåsplint. Må kun anvendes i brugsklasse 2 og 3 jf. DS/EN335-1."

2) I advarselsfeltet:

"FORSIGTIG

Skadelig for vandlevende organismer, med langvarige virkninger (H412)

Vær opmærksom på Arbejdstilsynets regler for arbejdets udførelse og personlige værnemidler. Læs nærmere i den eventuelt lovpligtige leverandør brugsanvisning.

Vask huden efter arbejdet.

Overtrædelse af nedenstående særligt fremhævede forskrifter kan medføre straf:

Må kun anvendes over jord til træbeskyttelse mod blåsplint. Må kun anvendes i brugsklasse 2 og 3 jf. DS/EN335-1.

Må kun anvendes i doseringer på 250-300 ml/m² ved industriel sprøjtning.

Må ikke anvendes mod andre skadevoldere og ikke i højere doseringer end de i brugsanvisningen nævnte.

Må ikke anvendes til træværk, der kommer i direkte berøring med fødevarer og foderstoffer.

Behandlet træ må indendørs kun bruges til vinduesrammer og yderdøre.

Opbevares utilgængeligt for børn.

Må ikke opbevares sammen med fødevarer, drikkevarer og foderstoffer.

Nyligt behandlet træ skal efter behandlingen henstilles overdækket eller på et hårdt og uigennemtrængeligt underlag for at forebyggedirekte spild til jord og vand

Eventuelt spild skal opsamles til genbrug eller bortskaffelse. ”

Evt. oplysninger om førstehjælp.

3) I deklarationsfeltet:

- a) Teksten "Træbeskyttelsesmiddel BPR-nr. 825-8. Aktivstof og biocidholdigt produkt er godkendt efterbiocidforordningen (Forordning (EU) nr. 528/2012)".
- b) Oplysning om præparattype:"Væske" for dette præparat.
- c) Indholdet af aktivstoffet i vægtprocent og g/Lved 20 °C.
- d) Sætningen: "Indeholder IPBC samt 1,2-benzisothiazol-3(2H)-one, reaction mass of:5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). Kan udløse en allergisk reaktion."
- e) Sidste holdbarhedsdato. Denne dato må højst være to år efter produktionsdatoen. Etikettens dato kan udformes som en hen-visning til en produktionsdato andetsteds på emballagen.
- f) Batchnummer eller-betegnelse.
- g) Pakningsstørrelse i liter.

4) Brugsanvisningen skalrettes til efter bilag 3 og 4 til denne afgørelse og indeholde:

- a) Oplysninger om skadevoldere, anvendelsesområdeog doseringer.
- b) Følgende sætninger på en fremtrædende plads i brugsanvisningen:
"Rester og tomemballage bortskaffes i henhold til de kommunale affaldsregulativer".