

Summary of product characteristics for a biocidal product

Product name: HSL-30/m

Product type(s): PT08 - Wood preservatives (Preservatives)

PT08 - Wood preservatives (Preservatives)

Authorisation number: 692-9

R4BP 3 asset reference number: DK-0012311-0001

Table Of Contents

Administrative information	1
1.1. Trade names of the product	1
1.2. Authorisation holder	1
1.3. Manufacturer(s) of the biocidal products	1
1.4. Manufacturer(s) of the active substance(s)	1
2. Product composition and formulation	2
2.1. Qualitative and quantitative information on the composition of the biocidal product	2
2.2. Type of formulation	2
3. Hazard and precautionary statements	3
4. Authorised use(s)	3
5. General directions for use	7
5.1. Instructions for use	7
5.2. Risk mitigation measures	7
5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment	8
5.4. Instructions for safe disposal of the product and its packaging	9
5.5. Conditions of storage and shelf-life of the product under normal conditions of storage	9
6. Other information	9

Administrative information

1.1. Trade names of the product

HSL-30/m

1.2. Authorisation holder

Name and address of the authorisation holder	Name	Remmers GmbH
	Address	Bernhard-Remmers-Str. 13 D - 49624 Lönigen Germany
Authorisation number	692-9 1-1	

R4BP 3 asset reference number	DK-0012311-0001
Date of the authorisation	23/06/2015
Expiry date of the authorisation	30/10/2025

1.3. Manufacturer(s) of the biocidal products

Name of the manufacturer	Remmers GmbH
Address of the manufacturer	Bernhard-Remmers-Straße 13 49624 Lönigen Germany
Location of manufacturing sites	Bernhard-Remmers-Straße 13 49624 Lönigen Germany

1.4. Manufacturer(s) of the active substance(s)

Active substance	39 - 3-iodo-2-propynylbutylcarbamate (IPBC)
Name of the manufacturer	Troy Chemical Company BV
Address of the manufacturer	Uiverlaan 12E 3145 XN Maassluis Netherlands
Location of manufacturing sites	One Avenue L NJ, 07105 Newark United States

2. Product composition and formulation

2.1. Qualitative and quantitative information on the composition of the biocidal product

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		Active Substance	55406-53-6	259-627-5	1,5
Propan-2-ol		Non-active substance	67-63-0		0,1
Naphtha (petroleum), hydrotreated heavy	Naphtha (petroleum), hydrotreated heavy	Non-active substance	64742-48-9	918-481-9	47,2202
Hydrocarbons, C9, aromatics / Solvent naphtha (petroleum), light arom. (Benzene < 0,1 %)		Non-active substance	64742-95-6	918-668-5	0,102
low boiling point hydrogen treated naphtha		Non-active substance	64742-82-1		0,337
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics		Non-active substance		920-360-0	18
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics		Non-active substance		927-632-8	0
Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified		Non-active substance	64742-94-5	265-198-5	0
Xylene, mixture of isomers		Non-active substance	1330-20-7	215-535-7	0,112
xylol, reaction mass of o-xylol, m-xylol, p-xylol and ethylbenzene		Non-active substance		905-588-0	0,28
Ethylbenzene		Non-active substance		202-849-4	0,048

2.2. Type of formulation

3. Hazard and precautionary statements

Hazard statements

May be fatal if swallowed and enters airways.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause damage to organs through prolonged or repeated exposure .
Harmful to aquatic life with long lasting effects.
Repeated exposure may cause skin dryness or cracking.

Precautionary statements

If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Do not breathe vapours.
Wear protective clothing.
Avoid release to the environment.
IF SWALLOWED:Immediately call a POISON CENTER.
Do NOT induce vomiting.
IF IN EYES:Rinse cautiously with water for several minutes.Remove contact lenses, if present and easy to do. Continue rinsing.
Store locked up.
Wear protective gloves.
Dispose of contents to in accordance with local/regional/national/international regulations...
IF ON SKIN:Wash with plenty of water.

4. Authorised use(s)

4.1 Use description

Use 1 - Preventive protection against wood-destroying and blue-staining fungi - professional use

Product type

PT08 - Wood preservatives (Preservatives)

Where relevant, an exact description of the authorised use

Preventive protection against wood destroying and blue stain fungi by spraying, and brushing in use class 2 and 3.

Target organism(s) (including development stage)

Scientific name: Aureobasidium pullulans spp.
Common name: Blue stain fungi
Development stage: Hyphae

Scientific name: Basidiomycetes:
Common name: Wood rotting basidiomycetes
Development stage: Hyphae

Field(s) of use

Outdoor

Preventive protection against wood-destroying and blue stain fungi in UC 2 and 3 according to EN 335

Application method(s)

Method: Open system: brush treatment

Detailed description:

Target organisms: wood rotting fungi, blue stain fungi

Field of use: Use Phase of treated Wood in Use Classes 2 and 3 acc. to EN 335, site of product application: outdoors, partly in situ

Method: Spraying

Detailed description:

only in closed facilities

Target organisms: wood rotting fungi, blue stain fungi

Field of use: use Phase of treated wood in UC 2 and 3 according to EN 335, site of product application only at industrial indoor work places, no in situ application

Application rate(s) and frequencies

Application Rate: 205-250 ml/m²

Dilution (%): Ready-to-use product

Number and timing of application:

Apply at least 2 subsequent coats. Drying-time brushing: Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower temperature and higher

Application Rate: 205-250 ml/m²

Dilution (%): ready-to-use product

Number and timing of application:

Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower temperature and higher humidity.)

Category(ies) of users

Trained professional

Professional

Pack sizes and packaging material

Can /Tin, Metal: , 0.75 L, 2.5 L, 5 L, 10 L, 20 L

Coated Tin Plate

4.1.1 Use-specific instructions for use

See section 5.1 below

4.1.2 Use-specific risk mitigation measures

Do not apply near bodies of surface water or in the area of water protection zone.
During in-situ application to timbers and whilst surfaces are drying, do not contaminate soil. All losses of the product have to be contained (by covering the soil) and disposed of in a safe way.
Wear protective chemical resistant gloves during product handling phase (glove material to be specified by the authorisation holder within the product information). A protective coverall (at least type 6, EN 13034) shall be worn. The use of eye protection during handling of the product is mandatory.

See section 5.2 below for further measures.

4.1.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

See section 5.3 below

4.1.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

See section 5.4 below

4.1.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

See section 5.5 below

4.2 Use description

Use 2 - Preventive protection against wood-destroying and blue stain fungi - industrial use

Product type

PT08 - Wood preservatives (Preservatives)

Where relevant, an exact description of the authorised use

Preventive protection against wood destroying and blue stain fungi by spraying, flow-coating and dipping in use class 2 and 3

Target organism(s) (including development stage)

Scientific name: *Aureobasidium pullulans* spp.
Common name: Blue stain fungi
Development stage: Hyphae

Scientific name: Basidiomycetes:
Common name: Wood rotting basidiomycetes
Development stage: Hyphae

Field(s) of use	<p>Outdoor</p> <p>Target organism: preventive protection against wood-destroying and blue-staining fungi in UC 2 and 3 according to EN 335</p>
Application method(s)	<p>Method: Open system: dip treatment Detailed description: Target organisms: wood rotting fungi, blue stain fungi Field of use: use Phase of treated Wood in UC 2 and 3 according to EN 335, site of product application only at industrial indoor work places, no in situ application</p> <p>Method: Open system: deluging Detailed description: flow coating Target organisms: wood rotting fungi, blue stain fungi Field of use: use Phase of treated Wood in UC 2 and 3 according to EN 335, site of product application only at industrial indoor work places, no in situ application</p> <p>Method: Spraying Detailed description: only in closed facilities Target organisms: wood rotting fungi, blue stain fungi Field of use: use Phase of treated wood in UC 2 and 3 according to EN 335, site of product application only at industrial indoor work places, no in situ application</p>
Application rate(s) and frequencies	<p>Application Rate: 205-250 ml/m² Dilution (%): Ready-to-use product Number and timing of application: Drying time after application: Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower temperature and higher humidity.)</p> <p>Application Rate: 205-250 ml/m² Dilution (%): Ready-to-use product Number and timing of application: Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower temperature and higher humidity.)</p> <p>Application Rate: 205-250 ml/m² Dilution (%): Ready-to-use product Number and timing of application: Approximately 12 hours at 20°C/65% rel. humidity (increased drying time with lower temperature and higher humidity.)</p>
Category(ies) of users	<p>Industrial</p>
Pack sizes and packaging material	<p>Can /Tin, Metal: , 0.75 L, 2.5 L, 5 L, 10 L, 20 L</p> <p>Coated Tin Plate</p>

4.2.1 Use-specific instructions for use

See section 5.1 below

4.2.2 Use-specific risk mitigation measures

Industrial application shall be conducted within a contained area on impermeable hard standing. Wear protective chemical resistant gloves during product handling phase (glove material to be specified by the authorisation holder within the product information). A protective coverall (at least type 6, EN 13034) shall be worn. The use of eye protection during handling of the product is mandatory.

See section 5.2 below for further measures.

4.2.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

See section 5.3 below

4.2.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

See section 5.4 below

4.2.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

See section 5.5 below

5. General directions for use

5.1. Instructions for use

Application rate 205-250 ml/m² (180-220 g/m²).
Drying-time after application: Approximately 12 hours at 20 degrees C/65 % rel. humidity (increased drying time with lower temperature and higher humidity)
Clean tool immediately after use with a thinner.
Apply solvent-resistant skin protection cream to hands and arms before working to avoid skin cracking.
Only for use on softwood.

5.2. Risk mitigation measures

Use only in well ventilated areas
Do not use indoors except for external window frames and external doors.
Do not use on wood that comes in direct contact with food or feed.
Treated wood should not be intended for uses involving contact with food, feed or livestock.
Prevent any release to the environment during the product application phase as well as during the storage and transport of treated timber.
Freshly treated timber shall be stored after treatment under shelter or on impermeable hard standing, or both, to prevent direct losses to soil, sewer or water, and any losses of the product shall be collected for reuse or disposal.
Any contaminated water/soil shall be collected, contained and treated as hazardous waste.
Open and handle with care
Do not eat, drink or smoke while working
Avoid contact with eyes and skin
Keep away from food, beverages and animal feed
Wash hands before pauses and after work
Do not inhale gases/vapours
Keep ignition sources away. – do not smoke
Protect against electrostatic charges
Fumes can combine with air to form an explosive mixture
In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment. Short term filter device: Filter A/P2.
Eye protection: Tightly sealed safety glasses.

5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

Warnings: Irritating to eyes..
May cause sensitisation by skin contact.
Safety phrases: Keep out of the reach of children.
Keep away from food, drink and animal feedingstuffs
Avoid contact with skin
After contact with skin, wash immediately with plenty of soap and water.
Wear suitable gloves.
If swallowed, seek medical advice immediately and show this container on Label
General information:
Immediately remove any clothing soiled by the product. In case of irregular breathing or respiratory arrest, provide artificial respiration. If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
After inhalation:
Take affected persons into the open air and position comfortably. Seek medical treatment in case of complaints. In case of unconsciousness bring patient into stable side position for transport.
After skin contact:
Wash immediately with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
After eye contact
Rinse opened eye for several minutes under running water. Then consult doctor.
After swallowing:
Do not induce vomiting. Do not give anything to drink. Call a doctor immediately! Keep the person affected quiet.
Information for doctor:
The following symptoms may occur:
In case of prolonged/repeated exposure or in high concentrations:
Headache
Dizziness
Dry skin
Irritating effect on skin and eyes.
Inhalation may have an irritating effect on mucous membranes.
Danger: Long-term or repeated exposure may cause inflammation of the skin (dermatitis).
Treatment: Symptomatic treatment
To avoid dermatitis (skin inflammation), use skin cream.

Measures for environmental protection:
Do not allow product to reach sewage system or water bodies. Do not allow to enter the ground/soil.
Prevent from spreading (e.g. by confining or oil barrier). This product may not be allowed to reach surface water because it is toxic to aquatic environments.
Measures for cleaning/collecting:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable containers. Clean soiled surfaces with detergent. Treat washing liquid as special refuse. Place leaking containers in a marked drum or recovery drum. Ensure adequate ventilation.

5.4. Instructions for safe disposal of the product and its packaging

Disposal considerations

Recommendation:

Liquid material remains are to be disposed of at collection facilities for old varnishes. Do not dispose of together with household garbage. Do not allow product to reach sewage system. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue:

03 02 02 organochlorinated wood preservatives

Uncleaned packaging:

Recommendation:

Only completely empty containers may be recycled. Disposal must be made according to official regulations.

5.5. Conditions of storage and shelf-life of the product under normal conditions of storage

Store in cool location.

Store away from food.

Store cool and dry in tightly closed containers.

Store container in a well-ventilated position.

Protect from frost.

Protect from heat and direct sunlight.

Smoking is prohibited in storage rooms.

Shelf life: 2 years

6. Other information

The label of the product should contain the following information (in Danish):

III. Etiketten skal indeholde nedenstående oplysninger. Oplysninger i citationstegn skal angives ordret:

1) I hovedfeltet:

"Træbeskyttelsesmiddel

Må kun anvendes over jord til træbeskyttelse mod blåsplint og trædelæggende svamp. Må kun anvendes erhvervmæssigt i brugsklasse 2 og 3 jf. DS/EN335-1."

2) I advarselsfeltet:

"FARE

Kan være livsfarligt, hvis det indtages og kommer i luftvejene (H304)

Forårsager organskader (larynx) ved længerevarende eller gentagen eksponering (H373)

Kan forårsage allergisk hudreaktion (H317)

Forårsager alvorlig øjenirritation (H319)

Skadelig for vandlevende organismer, med langvarige virkninger (H412)

Gentagen kontakt kan give tør og revnet hud (EUH066)

Bær kemisk resistente beskyttelseshandsker ved brug af produktet." Handskematerialet skal angives af godkendelsesindehaveren i produktdatabladet.

"

Indånd ikke spray.

Undgå udledning til miljøet.

Vask huden grundigt efter brug.

Overtrædelse af nedenstående særligt fremhævede forskrifter kan medføre straf:

Må kun anvendes over jord til træbeskyttelse mod blåsplint og trædelæggende svamp. Må kun anvendes erhvervmæssigt i brugsklasse 2 og 3 jf. DS/EN335-1.

Må ikke anvendes mod andre skadevoldere og ikke i højere doseringer end de i brugsanvisningen nævnte.

Må kun anvendes i doseringer på 205-250 ml/m² til erhvervmæssig pensling, dypning, flow-coat proces og sprøjtning.

Må ikke anvendes til træværk, der kommer i direkte berøring med fødevarer og foderstoffer.

Produktet må tillige anvendes i den angivne dosering i fuldautomatiserede neddypningsprocesser, hvor alle trin i behandlings- og tørringsprocessen er mekaniserede, og ikke omfatter manuel håndtering, herunder når de behandlede artikler trans-porteres gennem dypetanken til drænings-/tørrings-om-rådet og lageret (hvis de ikke allerede er tørre på overfladen, inden de flyttes til lageret). Om nødvendigt skal de træartikler, der skal behandles, fastgøres helt (f.eks. med spændebånd eller fastspændingsanordninger) inden behandling og under neddypningsprocessen og må ikke håndteres manuelt, før overfladen på de behandlede artikler er tør.

Behandlet træ må indendørs kun bruges til vinduesrammer og yderdøre.

Må ikke anvendes indendørs.

Ved påførsel skal jorden afdækkes, således at eventuelt spild opsamles.

For at beskytte organismer, der lever i vand, må midlet ikke anvendes i umiddelbar nærhed af vandmiljøet (vandløb, søer m.v.).

Må ikke tømmes i kloakfløb.

Opbevares under lås og utilgængeligt for børn.

Må ikke opbevares sammen med fødevarer, drikkevarer og foderstoffer.

Nyligt behandlet træ skal efter behandlingen henstilles overdækket eller på et hårdt og uigennemtrængeligt underlag for at forebygge direkte spild til jord og vand.

Eventuelt spild skal opsamles til genbrug eller bortskaffelse.”

Farepiktogrammet GHS07 og GHS08.

Miljøstyrelsen henleder opmærksomheden på, at godkendelsesindehaver skal anføre oplysninger om førstehjælp, herunder:

”Hvis der er brug for lægehjælp, medbring da beholderen eller etiketten.

VED KONTAKT MED HUDEN: Vask med rigeligt vand.

I TILFÆLDE AF INDTAGELSE: Ring omgående til en GIFTINFORMATION/læge fremkald IKKE opkastning.

VED KONTAKT MED ØJNENE: Skyl forsigtigt med vand i flere minutter. Fjern eventuelle kontaktlinser, hvis dette kan gøres let.

Fortsæt skylning.”

3) I deklarationsfeltet:

a) Teksten ”Træbeskyttelsesmiddel BPR-nr. 692-9-1-x[1]. Aktivstoffet godkendt efter biociddirektivet (98/8/EF). Produktet er godkendt efter biocidforordningen (Forordning (EU) 528/2012)”.

b) Oplysning om præparattype: ”Væske” for dette præparat.

c) Indholdet af aktivstoffet i vægtprocent og g/L ved 20 °C.

d) Sætningen: ”Indeholder cykliske kulbrinte forbindelser.”

e) Udløbsdatoen skal anføres. Denne dato må højst være to år efter produktionsdatoen. Etikettens dato kan udformes som en hen-visning til en produktionsdato andetsteds på emballagen.

f) Batchnummer eller –betegnelse skal anføres.

g) Pakningsstørrelse i liter.

h) Godkendelsesindehavers navn og adresse.

4) Brugsanvisningen:

Oplysninger om skadevoldere, anvendelsesområde og doseringer.

Brugsanvisningen skal rettes til efter den vedlagte effektivitetsvurdering fra Teknologisk Institut, Træ og Miljø.

Følgende retningslinjer gælder i forhold til bortskaffelse.

”Indholdet/holderen bortskaffes i overensstemmelse med kommunale regler for affaldshåndtering.

Rester skal afleveres til den kommunale affaldsordning for farligt affald. Tomme beholdere kan bortskaffes med dagrenovationen.”