

**EN**

***ANNEX***

**SUMMARY OF PRODUCT CHARACTERISTICS FOR A BIOCIDAL PRODUCT**

Xyladecor Holzschutz-Lasur 2in1 (Nussbaum)-DK-en

**Product type(s)**

PT08: Wood preservatives

**Authorisation number:** 782-118 1-1

**R4BP asset number:** DK-0012365-0011

---

1. ADMINISTRATIVE INFORMATION .....	3
1.1. Trade name(s) of the product .....	3
1.2. Authorisation holder .....	3
1.3. Manufacturer(s) of the product .....	3
1.4. Manufacturer(s) of the active substance(s) .....	3
2. PRODUCT COMPOSITION AND FORMULATION .....	4
2.1. Qualitative and quantitative information on the composition of the product .....	4
2.2. Type(s) of formulation .....	4
3. HAZARD AND PRECAUTIONARY STATEMENTS .....	5
4. AUTHORISED USE(S) .....	6
4.1. Use description .....	6
4.2. Use description .....	7
5. GENERAL DIRECTIONS FOR USE .....	9
5.1. Instructions for use .....	9
5.2. Risk mitigation measures .....	9
5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment .....	9
5.4. Instructions for safe disposal of the product and its packaging .....	9
5.5. Conditions of storage and shelf-life of the product under normal conditions of storage .....	9
6. OTHER INFORMATION .....	10

## 1. ADMINISTRATIVE INFORMATION

### 1.1. Trade name(s) of the product

Trade name(s)	Xyladecor Holzschutz-Lasur 2in1 (Nussbaum) Xyladecor Holzschutz-Lasur 2in1 (Nussbaum)
---------------	--

### 1.2. Authorisation holder

Name and address of the authorisation holder	Name	Akzo Nobel Decorative Coatings B.V.
	Address	Christian Neefestraat 2 - Attn. Director PSRAQ 1077 WW Amsterdam Netherlands
Authorisation number	782-118 1-1	
<i>R4BP asset number</i>	DK-0012365-0011	
Date of the authorisation	29/06/2015	
Expiry date of the authorisation	30/10/2025	

### 1.3. Manufacturer(s) of the product

Name of manufacturer	Akzo Nobel Decorative Paints Sp.z.o.o.
Address of manufacturer	ul. Wybrzeze Gdyskie 6d 01-531 Warszawa Poland
Location of manufacturing sites	ul. Przemyslowa 3 08-440 Pilawa Poland

Name of manufacturer	Akzo Nobel Decorative Paints SA
Address of manufacturer	Z.I. "Les Bas Prés", C.S. 60160 Montataire France
Location of manufacturing sites	Z.I. "Les Bas Prés", C.S. 60160 Montataire France

### 1.4. Manufacturer(s) of the active substance(s)

Active substance	3-iodo-2-propynylbutylcarbamate (IPBC)
Name of manufacturer	TROY Chemical Corporation
Address of manufacturer	8 Vreeland Road, Florham Park 07932 New Jersey United States (the)
Location of manufacturing sites	One Avenue L NJ 07105 Newark Netherlands (the)

---

## 2. PRODUCT COMPOSITION AND FORMULATION

### 2.1. Qualitative and quantitative information on the composition of the product

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		active substance	55406-53-6	259-627-5	0,7

### 2.2. Type(s) of formulation

Liquid wood preservative stain including colorless wood primer

---

### 3. HAZARD AND PRECAUTIONARY STATEMENTS

Hazard statements	H412: Harmful to aquatic life with long lasting effects.  EUH066: Repeated exposure may cause skin dryness or cracking.  EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.
Precautionary statements	P101: If medical advice is needed, have product container or label at hand.  P102: Keep out of reach of children.  P501: Dispose of container to local waste disposal collection point.  P273: Avoid release to the environment.  P501: Dispose of contents to local waste disposal collection point.

## 4. AUTHORISED USE(S)

### 4.1. Use description

**Table 1. Professional Use**

Product type	PT08: Wood preservatives
Where relevant, an exact description of the authorised use	For all outside wood which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), exterior doors (inner and outer parts), carports, shutters and balcony railings. Not for indoor use. The colorless version can be additionally used as a primer only and afterwards topcoated with a non-biocidal paint.
Target organism(s) (including development stage)	Scientific name: Aureobasidium pullulans spp. Common name: sapstain fungi Development stage: no data
Field(s) of use	outdoor use
Application method(s)	Method: open system: brush treatment  Detailed description: Brushing by professional users.
Application rate(s) and frequency	Application Rate: 160 - 200 ml/m <sup>2</sup> (146 - 183 g/m <sup>2</sup> )  Dilution (%): 0  Number and timing of application: 2 - 3 coats (depending on wood species)
Category(ies) of users	professional
Pack sizes and packaging material	Can /Tin, Metal: 0.375L, 0.75L, 1L, 2.5L, 5L, 6L, 7.5L, 10L, 20L

#### 4.1.1. Use-specific instructions for use

Wood surfaces must be clean and dry before treating. Keep freshly treated wood roofed or otherwise protected against rain until complete dryness. Handle product and freshly treated wood in areas with good ventilation. Do not breathe sanding dust.

See directions for use

#### 4.1.2. Use-specific risk mitigation measures

Keep away from food, drink and animal feeding stuffs.

See directions for use

#### 4.1.3. Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see 5.3 - Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

#### 4.1.4. Where specific to the use, the instructions for safe disposal of the product and its packaging

see 5.4 - Instructions for safe disposal of the product and its packaging

#### 4.1.5. Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see 5.5 - Conditions of storage and shelf-life of the product under normal conditions of storage

## 4.2. Use description

**Table 2. Nonprofessional Use**

Product type	PT08: Wood preservatives
Where relevant, an exact description of the authorised use	For all outside wood which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), exterior doors (inner and outer parts), carports, shutters and balcony railings. Not for indoor use. The colorless version can be additionally used as a primer only and afterwards topcoated with a non-biocidal paint.
Target organism(s) (including development stage)	Scientific name: Aureobasidium pullulans spp. Common name: sapstain fungi Development stage: no data
Field(s) of use	outdoor use
Application method(s)	Method: open system: brush treatment  Detailed description: Brushing by non-professional users.
Application rate(s) and frequency	Application Rate: 160 - 200 ml/m <sup>2</sup> (146 - 183 g/m <sup>2</sup> )  Dilution (%): 0  Number and timing of application: 2 - 3 coats (depending on wood species)
Category(ies) of users	general public (non-professional)
Pack sizes and packaging material	Can /Tin, Metal: 0.375L, 0.75L, 1L, 2.5L, 5L, 6L, 7.5 L

### 4.2.1. Use-specific instructions for use

Wood surfaces must be clean and dry before treating. Keep freshly treated wood roofed or otherwise protected against rain until complete dryness. Handle product and freshly treated wood in areas with good ventilation. Do not breathe sanding dust.

See directions for use

### 4.2.2. Use-specific risk mitigation measures

Keep away from food, drink and animal feeding stuffs.

See directions for use

### 4.2.3. Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

see 5.3 - Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

### 4.2.4. Where specific to the use, the instructions for safe disposal of the product and its packaging

see 5.4 - Instructions for safe disposal of the product and its packaging

### 4.2.5. Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

see 5.5 - Conditions of storage and shelf-life of the product under normal conditions of storage

---



---

## 5. GENERAL DIRECTIONS FOR USE<sup>1</sup>

### 5.1. Instructions for use

Always read the label or leaflet before use and follow all the instructions provided.

Xyladecor Holzschutz-Lasur 2in1 BPF

For all outside wood which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), exterior doors (inner and outer parts), carports, shutters and balcony railings. Not for indoor use. Ready to use. Do not thin. Stir well before use. Wood surfaces must be clean and dry before treating. Processing temperature is 5 - 35°C. The drying time is 12 - 24 hours (20°C / 65% rel. humidity).

Do not apply near bodies of surface water or in the area of water protection zones.

### 5.2. Risk mitigation measures

Xyladecor Holzschutz-Lasur 2in1 BPF

Keep freshly treated wood roofed or otherwise protected against rain until complete dryness.

Handle product and freshly treated wood in areas with good ventilation. Do not breathe sanding dust. Clean tools after use with commercial brush cleaner.

Keep away from food, drink and animal feeding stuffs.

In-situ application:

- Do not apply near bodies of surface water or in the area of water protection zones.
- During in-situ application to timbers and whilst surfaces are drying, do not contaminate soil. All losses of the product have to be contained (e.g. by appropriate covering of soil with a tarpaulin) and disposed of in a safe way
- Application solutions must be collected and reused or disposed of as hazardous waste. They must not be released to soil, ground- and surface water or any kind of sewer.

### 5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

Xyladecor Holzschutz-Lasur 2in1 BPF

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.

After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur.

If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs the head should be kept low so that vomit does not enter the lungs. Get medical attention.

After inhalation: Move affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

### 5.4. Instructions for safe disposal of the product and its packaging

Xyladecor Holzschutz-Lasur 2in1

European Waste Code (EWC): 03 02 05: other wood preservatives containing dangerous substances / 20 01 27: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions: paint, inks, adhesives and resins containing dangerous substances.

### 5.5. Conditions of storage and shelf-life of the product under normal conditions of storage

Xyladecor Holzschutz-Lasur 2in1 BPF

Store product in tightly closed original containers at temperatures about 5 - 30°C.

The product is stable for 2 years at room temperature.

---

<sup>1</sup>Instructions for use, risk mitigation measures and other directions for use under this section are valid for any authorised uses.

---

## 6. OTHER INFORMATION

Xyladecor Holzschutz-Lasur 2in1 BPF, DK

Xyladecor Classic HP (BPR), CZ

Xyladecor Classic HP (BPR), SK

Xyladecor Holzschutz-Lasur 2in1, DE

Sikkens Cetol Aktiva(BPR), DE, AT, CH

Herbol Bläueschutz-Grund(BPR), DE, AT, CH

Xyladecor Holzschutz-Grundierung(BPR), AT, CH

Bilag 1 Oplysninger til etiket og brugsanvisning for Xyladecor Holzschutz-Lasur 2 in 1, BPR-reg. nr. 782-118-1

I. Etiketten skal udformes i overensstemmelse med artikel 69 i biocidforordningen (Forordning (EU) nr. 528/2012), og CLP Forordningen[1].

II. Det er udelukkende ansøgers/godkendelsesindehaverens ansvar, at etiket, mærkning og pakning lever op til lovens krav, jf. biocidforordningen artikel 69.

Nedstående tekst i afsnit III er bidrag til overholdelsen af reglerne og således kun en del af de krav, som stilles til blandt andet etiketten.

III. Etiketten skal indeholde nedenstående oplysninger. Oplysninger i citationstegn skal angives ordret:

1) I hovedfeltet:

”Træbeskyttelsesmiddel (PT8)

Må kun anvendes over jord til træbeskyttelse mod blåsplint. Må kun anvendes i brugsklasse 2 og 3 jf. DS/EN335-1.”

2) I advarselsfeltet:

”**FORSIGTIG**

Skadelig for vandlevende organismer, med langvarige virkninger (H412).

Undgå udledning til miljøet (P273).

Vask huden efter arbejdet.

Vær opmærksom på, at Arbejdstilsynet har regler for arbejde med bekæmpelsesmidler. Læs nærmere i det eventuelt lovpligtige sikkerhedsdatablad samt i Arbejdstilsynets informationsmateriale om bekæmpelsesmidler. Overtrædelse af nedenstående særligt fremhævede forskrifter kan medføre straf:

**Må kun anvendes til træbeskyttelse mod blåsplint. Må kun anvendes i brugsklasse 2 og 3 jf. DS/EN335-1.**

**Må kun anvendes i doseringer på 160-200 ml/m<sup>2</sup> ved pensling.**

**Må ikke anvendes mod andre skadevoldere og ikke i højere doseringer end de i brugsanvisningen nævnte.**

**Må ikke anvendes til træværk, der kommer i direkte berøring med fødevarer og foderstoffer.**

**Må ikke anvendes indendørs.**

**Må ikke tømmes i kloak afløb.**

**Opbevares utilgængeligt for børn.**

**Må ikke opbevares sammen med fødevarer, drikkevarer og foderstoffer.”**

Evt. oplysninger om førstehjælp.

VED KONTAKT MED HUDEN: Vask med rigeligt vand (P302+P352)

3) I deklarationsfeltet:

a) Teksten ”Træbeskyttelsesmiddel BPR-reg. nr. 782-118-1. Aktivstof og biocidholdigt produkt er godkendt efter biociddirektivet (98/8/EF)”.

b) Oplysning om præparattype: ” væske” for dette præparat.

c) Indholdet af aktivstof i vægtprocent og g/L ved 20 °C.

d) Sætningen: ”Indeholder IPBC. Kan udløse allergisk reaktion (EUH208)”.

”Gentagen kontakt kan give tør eller revnet hud (EUH066)”.

e) Udløbsdatoen skal anføres. Denne dato må højst være 2 år efter produktionsdatoen. Etikettens dato kan udformes som en henvisning til en produktionsdato andetsteds på emballagen.

f) Batchnummer eller – betegnelse skal anføres.

g) Pakningsstørrelse i liter.

h) Godkendelsesindehavers navn og adresse.

4) Brugsanvisningen:

Oplysninger om skadevoldere, anvendelsesområde og doseringer.

Følgende retningslinjer gælder i forhold til bortskaffelse.

Der skal mærkes med sikkerhedssætning P501: ”Indholdet/holderen bortskaffes i overensstemmelse med kommunale regler for affaldshåndtering.”

Derudover skal mærkningen ske efter følgende retningslinjer:

---

Rester og tom emballage bortskaffes i henhold til de kommunale affaldsregulativer.