

Summary of product characteristics for a biocidal product

Product name: Sikkens Rubbol WP 177 (BPD)

Product type(s): PT08 - Wood preservatives (Preservatives)

Authorisation number: BPD-reg. nr. 825-10

R4BP 3 asset reference number: DK-0001686-0000

Table Of Contents

Administrative information	1
1.1. Trade names of the product	1
1.2. Authorisation holder	1
1.3. Manufacturer(s) of the biocidal products	1
1.4. Manufacturer(s) of the active substance(s)	1
2. Product composition and formulation	2
2.1. Qualitative and quantitative information on the composition of the biocidal product	2
2.2. Type of formulation	2
3. Hazard and precautionary statements	2
4. Authorised use(s)	2
5. General directions for use	4
5.1. Instructions for use	4
5.2. Risk mitigation measures	4
5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment	4
5.4. Instructions for safe disposal of the product and its packaging	4
5.5. Conditions of storage and shelf-life of the product under normal conditions of storage	5
6. Other information	5

Administrative information

1.1. Trade names of the product

Rubbol WP 177

1.2. Authorisation holder

Name and address of the authorisation holder

Name	Akzo Nobel Industrial Coatings AB
Address	Staffanstorpsvägen 50 20517 Malmö Sweden
Authorisation number	BPD-reg. nr. 825-10
R4BP 3 asset reference number	DK-0001686-0000
Date of the authorisation	25/11/2011
Expiry date of the authorisation	30/10/2025

1.3. Manufacturer(s) of the biocidal products

Name of the manufacturer

Akzo Nobel Industrial Coatings AB

Address of the manufacturer

Staffanstorpsvägen 50 20517 Malmö Sweden
--

Location of manufacturing sites

Akzo Nobel Industrial Coatings AB 20517 Malmö Sweden
--

1.4. Manufacturer(s) of the active substance(s)

Active substance	39 - 3-iodo-2-propynylbutylcarbamate (IPBC)
Name of the manufacturer	Troy Corporation
Address of the manufacturer	8 Vreeland Road, Florham Park 07932 New Jersey United States
Location of manufacturing sites	One Avenue L NJ 07105 Newark United States

2. Product composition and formulation

2.1. Qualitative and quantitative information on the composition of the biocidal product

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
3-iodo-2-propynylbutylcarbamate (IPBC)		Active Substance	55406-53-6	259-627-5	0,6

2.2. Type of formulation

water based primer

3. Hazard and precautionary statements

Hazard statements	Harmful to aquatic life with long lasting effects. Contains 1,2-benzisothiazol-3(2H)-one, CMIT/MIT, IPBC. May produce an allergic reaction.
Precautionary statements	Avoid release to the environment. Dispose of container to in accordance with all local, regional and international regulations.

4. Authorised use(s)

4.1 Use description

Use 1 - Redy-to -use wood preservative primer, water based

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), carports, shutters and balcony railings. Not for indoor use. Authorisation is granted for Use Class 2 and Use Class 3.
Target organism(s) (including development stage)	Scientific name: Aureobasidium pullulans spp. Common name: Sapstain fungi Development stage:
Field(s) of use	Outdoor For all outside wood, which is not in direct contact to soil or surface water and not stressed statically, e.g. facades, windows (inner and outer parts), carports, shutters and balcony railings. Not for indoor use.
Application method(s)	Dipping and deluging - Wood surfaces must be clean and dry before treating. Handle product and dry freshly treated wood in areas with good ventilation. Keep freshly treated wood roofed or otherwise protected against rain until complete dryness. Do not breathe sanding dust. The stain is ready to use. Do not thin. Stir well before use. Apply by dipping and/or deluging. Reseal container after use. Processing temperature is 5-25°C. Apply 120-160 ml/m ² (122-162 g/m ²). The drying time is 4-6 hours (20°C/65% rel. Humidity). A top-coat should be applied.
Application rate(s) and frequencies	Apply 120-160 ml/m ² (122-162 g/m ²) - No dilution - Apply 120-160 ml/m ² (122-162 g/m ²)
Category(ies) of users	Industrial
Pack sizes and packaging material	Can /Tin, Metal: , 20 L Can /Tin, Plastic: HDPE , 120 L Can /Tin, Plastic: HDPE , 1000L

4.1.1 Use-specific instructions for use

Wood surfaces must be clean and dry before treating. Handle product and dry freshly treated wood in areas with good ventilation. Keep freshly treated wood roofed or otherwise protected against rain until complete dryness. Do not breathe sanding dust. The stain is ready to use. Do not thin. Stir well before use. Apply by dipping and/or deluging. Reseal container after use. Processing temperature is 5-25°C. Apply 120-160 ml/m² (122-162 g/m²). The drying time is 4-6 hours (20°C/65% rel. Humidity). A top-coat should be applied.

4.1.2 Use-specific risk mitigation measures

Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs. Avoid contact with skin and eyes. Wear suitable protective clothing, gloves and eye/face protection.

4.1.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

After skin contact: Take off immediately all contaminated clothing and wash skin immediately with plenty of water and soap. Obtain medical attention if symptoms occur.
After contact with eyes: Rinse immediately with plenty of water and seek medical if symptoms occur.
If swallowed: Do not induce vomiting unless expressly instructed by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.
After inhalation: Move the affected person into fresh air. Keep person warm and at rest. Provide artificial respiration by trained person if breathing is irregular or arrested. Seek medical advice if symptoms are severe or long lasting. If unconscious place in recovery position and get medical attention immediately.

4.1.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

Instructions for safe disposal of the product and its packaging: European waste code (EWC):
02 0205: other wood preservatives containing dangerous substances / 20 0127: Municipal wastes (household, waste and similar commercial, industrial and institutional wastes) including separately collected fractions:
paint, inks, adhesives and resins containing dangerous substances.

4.1.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

Store product in tightly closed original containers at temperatures about 5 - 30°C. The product is stable for 2 years at room temperature.

5. General directions for use

5.1. Instructions for use

See Authorised Uses

5.2. Risk mitigation measures

See Authorised Uses

5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

See Authorised Uses

5.4. Instructions for safe disposal of the product and its packaging

See Authorised Uses

5.5. Conditions of storage and shelf-life of the product under normal conditions of storage

See Authorised Uses

6. Other information

Use biocides safely. Always read label and product information before use.