

Summary of product characteristics for a biocidal product

Product name: Wolmanit CX-8WB

Product type(s): PT08 - Wood preservatives (Preservatives)

Authorisation number: 660-6

R4BP 3 asset reference number: DK-0013103-0001

Table Of Contents

Administrative information	1
1.1. Trade names of the product	1
1.2. Authorisation holder	1
1.3. Manufacturer(s) of the biocidal products	1
1.4. Manufacturer(s) of the active substance(s)	1
2. Product composition and formulation	2
2.1. Qualitative and quantitative information on the composition of the biocidal product	2
2.2. Type of formulation	2
3. Hazard and precautionary statements	3
4. Authorised use(s)	3
5. General directions for use	6
5.1. Instructions for use	6
5.2. Risk mitigation measures	6
5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment	7
5.4. Instructions for safe disposal of the product and its packaging	8
5.5. Conditions of storage and shelf-life of the product under normal conditions of storage	8
6. Other information	9

Administrative information

1.1. Trade names of the product

Wolmanit CX-8WB
Wolmanit CX-8M

1.2. Authorisation holder

Name and address of the authorisation holder	Name	Wolman Wood and Fire Protection GmbH
	Address	Dr.-Wolman-Strasse 31-33 Wolman Registrierung WR 76547 Sinzheim Germany
Authorisation number	660-6 1-1	

R4BP 3 asset reference number

DK-0013103-0001

Date of the authorisation

19/04/2021

Expiry date of the authorisation

29/03/2031

1.3. Manufacturer(s) of the biocidal products

Name of the manufacturer	Wolman Wood and Fire Protection GmbH
Address of the manufacturer	Dr.-Wolman-Strasse 31-33 76547 Sinzheim Germany
Location of manufacturing sites	Dr.-Wolman-Strasse 31-33 76547 Sinzheim Germany

1.4. Manufacturer(s) of the active substance(s)

Active substance	1279 - Cu-HDO
Name of the manufacturer	BASF SE
Address of the manufacturer	Carl-Bosch-Straße 38 67056 Ludwigshafen Germany
Location of manufacturing sites	Carl-Bosch-Straße 38 67056 Ludwigshafen Germany
Active substance	6 - Basic Copper carbonate
Name of the manufacturer	Spiess-Uranial Chemicals GmbH
Address of the manufacturer	Frankenstrasse 18 b 20097 Hamburg Germany
Location of manufacturing sites	Frankenstrasse 18 b 20097 Hamburg Germany

2. Product composition and formulation

2.1. Qualitative and quantitative information on the composition of the biocidal product

Common name	IUPAC name	Function	CAS number	EC number	Content (%)
Cu-HDO		Active Substance	312600-89-8		2,8
Basic Copper carbonate	Copper(II) carbonate-copper(II) hydroxide (1:1)	Active Substance	12069-69-1	235-113-6	13,04
2-Aminoethanol	2-Aminoethanol; ethanolamine	Non-active substance	141-43-5	205-483-3	28,6
2-Ethylhexanoic acid	2-Ethylhexanoic acid	Non-active substance	149-57-5	205-743-6	4,9
n-Heptanoic acid	n-Heptanoic acid	Non-active substance	111-14-8	203-838-7	3,1
Polyethyleneimine (50 % in water)	Polyethyleneimine (50 % in water)	Non-active substance	9002-98-6	618-346-1	6

2.2. Type of formulation

SL - Soluble concentrate

3. Hazard and precautionary statements

Hazard statements

Harmful if swallowed.
Harmful if inhaled.
Causes severe skin burns and eye damage.
Corrosive to the respiratory tract.
Contains polyethyleneimine.. May produce an allergic reaction.
Suspected of damaging the unborn child.
Very toxic to aquatic life with long lasting effects.

Precautionary statements

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep only in original packaging.
Do not breathe spray.
Wash hands thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Avoid release to the environment.
Wear protective gloves.
IF SWALLOWED:Rinse mouth.Do NOT induce vomiting.
IF ON SKIN (or hair):Take off immediately all contaminated clothing.Rinse skin with water.
IF INHALED:Remove person to fresh air and keep comfortable for breathing.
Immediately call a POISON CENTER.
IF IN EYES:Rinse cautiously with water for several minutes.Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned:Get medical advice.
Absorb spillage to prevent material damage.
Collect spillage.
Store locked up.

4. Authorised use(s)

4.1 Use description

Use 1 - Use 1 - Fungi, beetles, termites – industrial users – vacuum/oscillating pressure treatment - indoor

Product type	PT08 - Wood preservatives (Preservatives)
Where relevant, an exact description of the authorised use	---
Target organism(s) (including development stage)	<p>Scientific name: Wood destroying fungi Common name: Brown rot fungi Development stage:</p> <p>Scientific name: Wood destroying fungi Common name: White rot fungi Development stage:</p> <p>Scientific name: Wood destroying fungi Common name: Soft rot fungi Development stage:</p> <p>Scientific name: Wood boring beetles Common name: Wood destroying beetles Development stage: Larvae</p> <p>Scientific name: Termites (subterranean termites): Reticulitermes spp. Common name: Termites Development stage:</p>
Field(s) of use	<p>Indoor</p> <p>Application: indoor use in dedicated treatment plants</p> <p>Preservation of structural timber for indoor and outdoor use, in particular for timber used in use class 1, 2, 3 and 4, e.g. for horticulture and landscape gardening, posts, fences, palisades, playground equipment and wood paving including use class 4 special application for transmission poles with service live of 25-40 years. Please mind the restrictions.</p>
Application method(s)	<p>Method: Vacuum pressure treatment / oscillating pressure process Detailed description: APPLICATION RATES: <i>Without protection against termites:</i></p> <p>Product retention² [kg/m³]: UC1: 6.50 UC2: 7.85 UC3: 7.85 - 9.00 UC4: 10.90 - 22.50 UC4 special¹: 13.0 - 31.25</p> <p>Application Solution³ [% (w/w)]: UC1: 1.08 UC2: 1.30 UC3: 1.30 - 1.50 UC4: 1.82 - 3.75 UC4 special¹: 2.17 - 5.21</p> <p><i>With protection against termites:</i> Product retention² [kg/m³]: UC1: 13.10 UC2: 13.10 UC3: 13.81 UC4: 13.81-22.5</p>

UC4 special¹: 13.81-31.25

Application Solution³ [% (w/w)]:
UC1: 2.18
UC2: 2.18
UC3: 2.30
UC4: 2.30 - 3.75
UC4 special¹: 2.30 - 5.21

¹ The use class "UC 4 special" specifically targets treated timber with applications having an increased service life time (e.g. transmission poles). For the intended use class "UC 4 special" a service life between 25 and 40 years is to be expected.
² This refers to the undiluted product (i.e. concentrate) per volume of treated wood
³ Based on an average solution uptake of 600 L during vacuum pressure treatment

Application rate(s) and frequencies

Application Rate: 6.5 - 31.25 kg/m³
Dilution (%): 1.08 - 5.21
Number and timing of application:
Single application

Category(ies) of users

Industrial

Pack sizes and packaging material

30 L Jerrycan, HDPE
60 L Drum, HDPE
600 L IBC, HDPE
1000 L IBC, HDPE

For transport only:
30 000 L Bulk container (stainless steel)
no commercial packaging

4.1.1 Use-specific instructions for use

4.1.2 Use-specific risk mitigation measures

4.1.3 Where specific to the use, the particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

4.1.4 Where specific to the use, the instructions for safe disposal of the product and its packaging

4.1.5 Where specific to the use, the conditions of storage and shelf-life of the product under normal conditions of storage

5. General directions for use

5.1. Instructions for use

Apply the product via vacuum pressure / oscillating pressure treatment.
Dilute the product according to the application solution with water table via automated dosing.
The fixation time is minimum 48h.
Do not use on wood that may come in direct contact with food and feeding stuff.
Regard that efficacy assessment has been performed according to the reference wood *Pinus silvestris*.

5.2. Risk mitigation measures

The following personal protective equipment should be worn during product handling phase (application and cleaning):
Wear protective chemical resistant gloves during product handling phase (glove material to be specified by the authorisation holder within the product information).
A protective coverall (at least type 6, EN 13034) shall be worn.
Wear suitable protective footwear (EN 13832) when applying the product.
Wear a face shield when applying the product.

The process of dilution has to be carried out using an automatic dosing system.
Avoid contact with skin and eyes.
Handle product and dry freshly treated wood in areas with good ventilation.
Cleaning of the treatment chamber as well as pressure treatment of wood shall not be performed by the same operator on the same day.
All industrial application processes must be carried out within an area situated on impermeable hard standing with bunding to prevent run-off and a recovery system in place (e.g. sump).
Freshly treated timber must be stored after treatment under shelter or on impermeable hard standing, or both, to prevent direct losses to soil, sewer or water, and that any losses of the product, including any contaminated water/soil must be collected for reuse or disposal in accordance with local/national/international requirements.
The product must not be applied on wood for use class 4, that is foreseen to be placed directly in water bodies.

The following risk mitigation measures are added as an adjustment to terms and conditions in Denmark, pursuant to BPR article 37 (1), b and c. This derogation from mutual recognition has been agreed upon by the applicant on January 19th 2021, pursuant to BPR article 37 (2).

Not permitted for treatment of wood (treated articles) intended for Use Class 1 in buildings in Denmark with the exception of churches and the like, other buildings worthy of preservation, and other buildings where people do not work or stay for prolonged periods, and where such use does not result in risk of direct contact with treated wood.

Not permitted for treatment of wood (treated articles) intended for Use Class 2 in buildings in Denmark, with the exception of external doors and door frames and external window frames, and with the exception of churches and the like, other buildings worthy of preservation, and other buildings where people do not work or stay for prolonged periods.

Only for treatment against termites (high application rates), when the treated article is intended for export.

5.3. Particulars of likely direct or indirect effects, first aid instructions and emergency measures to protect the environment

First aid instructions:

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth or induce vomiting if a person is unconscious. If unconscious, place in recovery position and seek medical advice.

IF IN EYES: Immediately rinse eyes with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for 15 to 30 minutes. Seek immediate medical attention.

IF ON SKIN: Immediately wash skin with plenty of water. Thereafter take off immediately all contaminated clothing and shoes. Rinse skin with lukewarm, gently flowing water/shower for at least 15 to 30 minutes. Seek immediate medical attention.

IF SWALLOWED: Immediately rinse mouth. Give something to drink, if exposed person is able to swallow. Do NOT induce vomiting. Immediately seek medical advice. Seek immediate medical attention.

IF INHALED: Move to fresh air and keep at rest in a position comfortable for breathing. If symptoms: Call 112/ambulance for medical assistance. If no symptoms: Call a POISON CENTRE or a doctor

Emergency measures to protect the environment:

If the product contaminates lakes, rivers, sewers or soil, inform the appropriate authorities in accordance with local regulations.

Contain and collect spillage with an inert absorbent (e.g. sand, earth etc.). For large amounts: Pump off the product.

Dispose of contents/container to a special waste collection point in accordance with local/national/international requirements.

5.4. Instructions for safe disposal of the product and its packaging

Product residues, contaminated materials (including sawdust) and empty containers must be collected and disposed of in accordance with the national waste disposal legislation and any regional and/or local authority requirements.

Do not discharge the biocidal product nor the diluted solution of the biocidal product into the sewage system or the environment (in particular surface water).

5.5. Conditions of storage and shelf-life of the product under normal conditions of storage

The product must be stored only in original containers tightly closed and out of reach of unauthorised persons.
Recommended storage temperature range: $\geq 0^{\circ}\text{C}$ to $+ 40^{\circ}\text{C}$.¹
Protect from frost.
At low temperatures, crystallisation may occur. Redissolve precipitated ingredients by raising the temperature.
The shelf life of the product is 24 months.

Note:

¹ This recommendation is provided by the applicant. The accelerated storage test showed stability up to 54°C .

6. Other information

The SPC Editor technically does not allow the exact reflection of the precautionary Statements as given in the PAR.

This concerns the following entries:

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P310: Immediately call a POISON CENTER or doctor.

P308+P313: IF exposed or concerned: Get medical advice/attention.

Bilag 1.1 – (Meta-SPC 1)

Oplysninger til etiket og brugsanvisning for Wolmanit CX-8WB family, BPR-reg. nr. 660-6-1-x [1] .

I. Etiketten skal udformes i overensstemmelse med det godkendte resumé af det biocidholdige produkts egenskaber, jf. artikel 69, stk. 1, i biocidforordningen (Forordning (EU) nr. 528/2012), og CLP-Forordningen .

II. Det er udelukkende ansøgers/godkendelsesindehaverens ansvar, at etiket, mærkning og pakning lever op til lovens krav, jf. biocidforordningen artikel 69. Etiket og mærkning skal være på dansk.

Nedstående tekst i afsnit III er bidrag til overholdelsen af reglerne og således kun en del af de krav, som stilles til blandt andet etiketten.

III. Etiketten skal indeholde nedenstående oplysninger. Op-lys-ninger i citationstegn skal angives ordret:

1) I hovedfeltet:

”Træbeskyttelsesmiddel

Må kun anvendes til træbeskyttelse mod træødelæggende svamp, træborende biller og termitter (*Reticulitermes* spp.) ved industriel trykimprægning. Må kun anvendes i brugsklasse 1-4, jf. DS/EN335:2013.

2) I advarselsfeltet:

”**FARE**

Farlig ved indtagelse (H302).

Farlig ved indånding (H332).

Forårsager svære forbrændinger af huden og øjenskader (H314).

Mistænkes for at skade det ufødte barn (H361d).

Meget giftig med langvarige virkninger for vandlevende organismer (H410).

Ætsende for luftvejene (EUH071).

Indånd ikke tåge/damp/spray.

Bær beskyttelsestøj og ansigtsbeskyttelse. Bær kemisk resistente beskyttelseshandsker ved brug af produktet.”
Handskematerialet skal angives af godkendelsesindehaveren i produktdatabladet.

”Vask hænderne grundigt efter brug.

Der må ikke spises, drikkes eller ryges under brugen af dette produkt.

Opbevares under lås.

Undgå udledning til miljøet.

Udslip opsamlles.

Absorber udslip for at undgå materielskade.

Overtrædelse af nedenstående særligt fremhævede forskrifter kan medføre straf:

”Må kun anvendes til træbeskyttelse mod træødelæggende svamp, træborende biller og termitter (*Reticulitermes* spp.) ved industriel trykimprægning. Må kun anvendes i brugsklasse 1-4, jf. DS/EN335:2013.

Må ikke anvendes til behandling af træartikler tiltænkt brugsklasse 1 i bygninger i Danmark, med undtagelse af kirker o.l., andre bevaringsværdige bygninger samt bygninger, hvor mennesker ikke arbejder eller opholder sig i længere tid ad

gangen, og hvor sådan en anvendelse ikke giver risiko for direkte kontakt med det behandlede træ.
Må ikke anvendes til behandling af træartikler tilmålt brugsklasse 2 i bygninger i Danmark, med undtagelse af udvendige døre og dørrammer samt udvendige vinduesrammer, og med undtagelse af kirker o.l., andre bevaringsværdige bygninger samt bygninger, hvor mennesker ikke arbejder eller opholder sig i længere tid ad gangen.
Må kun anvendes til bekæmpelse af termitter, når det behandlede træ skal eksporteres.
Må ikke anvendes mod andre skadevoldere og ikke i højere doseringer end de i brugsanvisningen nævnte.
Må ikke anvendes til træværk, der kommer i direkte berøring med fødevarer og foderstoffer.
Må ikke tømmes i kloak afløb.
Der skal bæres en beskyttende heldragt (som minimum type 6, EN 13034). Brug egnet sikkerhedsfodtøj (EN 13832). Bær ansigtsskærm.
Fortyndingen skal udføres med et automatisk doseringssystem.
Rengøring af behandlingskammeret samt trykbehandling af træ må ikke udføres af den samme operatør samme dag.
Håndter produktet og tør friskbehandlet træ i områder med god ventilation.
Må ikke opbevares sammen med fødevarer, drikkevarer og foderstoffer.

Nyligt behandlet træ skal efter behandlingen henstilles overdækket eller på et hårdt og uigennemtrængeligt underlag for at forebygge direkte spild til jord og vand.

Eventuelt spild skal opsamles til genbrug eller bortskaffelse.
Må ikke anvendes til behandling af træ til brugsklasse 4, som skal anvendes direkte i vandmiljøet (vandløb, søer m.v.).
Ved udlevering fra imprægneringsanlæg skal alt træ være strøslagt. Strøer med en tykkelse af mindst 10 mm skal være lagt mellem hvert lag træ, hvis tykkelsen af det behandlede træ overstiger 32 mm. Hvis trætykkelsen er 32 mm eller mindre, må der lægges strøer for hvert andet lag træ. Træet kan udleveres klodslagt, hvis det er tørret ud til en middelfugtighed på højst 25 %.

Imprægneret træ skal påføres varig mærkning.”

Farepiktogrammet GHS05, GHS07, GHS08, GHS09.

Miljøstyrelsen henleder opmærksomheden på, at godkendelsesindehaver skal anføre oplysninger om førstehjælp, herunder:

I TILFÆLDE AF INDTAGELSE: Skyl munden. Fremkald IKKE opkastning.

VED KONTAKT MED HUDEN (eller håret): Alt tilsmudset tøj tages straks af. Skyl/brus huden med vand.

VED INDÅNDING: Flyt personen til et sted med frisk luft og sørg for, at vejrtrækningen lettes.

VED KONTAKT MED ØJNENE: Skyl forsigtigt med vand i flere minutter. Fjern eventuelle kontaktlinser, hvis dette kan gøres let. Fortsæt skylning.

Ring omgående til en GIFTINFORMATION/læge.

VED eksponering eller mistanke om eksponering: Søg lægehjælp.

Hvis der er brug for lægehjælp, medbring da beholderen eller etiketten.

3) I deklaraionsfeltet:

- a) Teksten ”Træbeskyttelsesmiddel BPR-reg. nr. 660-6-1-x[1]” . Aktivstoffer og biocidholdigt produkt er godkendt efter biocidforordningen (Forordning (EU) nr. 528/2012)”.
- b) Oplysning om præparattype: flydende koncentrat for dette præparat.
- c) Indholdet af aktivstoffer i vægtprocent (% w/w) og g/L ved 20 °C.
- d) Sætningen: ”Indeholder 2-aminoethanol, 2-ethylhexansyre, polyethylenimin og n-heptansyre.” og sætningen ”Indeholder polyethylenimin. Kan udløse allergisk reaktion.”
- e) Udløbsdatoen skal anføres. Denne dato må højst være to år efter produktionsdatoen. Etikettens dato kan udformes som en hen-visning til en produktionsdato andetsteds på emballagen.
- f) Batchnummer eller – betegnelse skal anføres.
- g) Pakningsstørrelse i L.
- h) Godkendelsesindehavers navn og adresse.

4) Brugsanvisningen:

Oplysninger om skadevoldere, anvendelsesområde og doseringer.

Følgende retningslinjer gælder i forhold til bortskaffelse.
Der skal mærkes med sikkerhedssætning P501: ”Indholdet/beholderen bortskaffes i overensstemmelse med kommunale regler for affaldshåndtering.”

Derudover skal mærkningen ske efter retningslinjerne:
”Rester skal afleveres til den kommunale affaldsordning for farligt affald.
Tomme beholdere kan bortskaffes med dagrenovationen.”

[1] "x" skal erstattes med et tal som angivet i godkendelsesbrevets bilag 4.